

# Taisite



**TAISITE LAB SCIENCES INC**



Anti-dry heating



Stamping chamber



Five rings lid

**Features**

1. Integrated stamped chamber, groove at bottom for better drainage;
2. Stainless steel 304 material chamber and shelf, better anti rust;
3. Five rings lid, more convenient for different sizes of glasswares;
4. Hidden drain tube, beautiful and easy to use;
5. Microcomputer PID control, accuracy 0.1°C;
6. With timer 0-9999min;
7. Triple safety function:
  - 1) Overcurrent protection;
  - 2) Over temperature alarm;
  - 3) Prevent dry burning function;
8. WBE series don't include anti dry burning

**Specifications**

Model(integrated chamber)	WB-1S	WB-2S	WB-4D	WB-6D
	WBE-1S	WBE-2S	WBE-4D	WBE-6D
Controller	PID			
Voltage	220V/50Hz 110V/60Hz			
Power(W)	300W	600W	600W	1200W
Tem-range(°C)	RT.+5~100°C			
Temperature resolution	0.1°C			
Temperature fluctuation	≤±0.5°C			
Division accuracy	≤±1°C			
Timer	999 minutes			
Safety	Overcurrent protection; Over temperature alarm; Prevent dry burning function;			
Chamber Size(mm)	160*160*130	305*160*130	305*305*130	470*305*130
Product Size(mm)	200*200*220	345*200*220	345*345*220	510*345*220
Packing Size(mm)	250*250*270	400*250*270	400*400*270	550*400*270
N.W/G.W	3KG/3.5KG	4KG/5KG	6KG/7KG	8KG/9KG



**Features**

1. TWB water tank is with deeper integrated chamber;
2. TWB water tank is with arched lid, which can hold higher bottles, test-tube rack, or erlenmeyer Flasks;

**Specifications**

Model(integrated chamber)	TWB-11D	TWB-22D	TWB-15D	TWB-30D
Controller	PID			
Voltage	220V/50Hz 110V/60Hz			
Power(W)	800W	1200W	1000W	1500W
Tem-range(°C)	RT.+5~100°C			
Temperature resolution	0.1°C			
Temperature fluctuation	≤±0.5°C			
Division accuracy	≤±1°C			
Timer	999 minutes			
Recycle Design	Null			
Safety	Overcurrent protection; Over temperature alarm; Prevent dry burning function;			
Chamber Size(mm)	300*240*150	500*290*150	300*240*200	500*290*200
Product Size(mm)	340*280*240	550*350*240	340*280*290	550*350*290
Packing Size(mm)	390*330*290	600*400*290	390*330*340	600*400*340